


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### LINE DRAWING



### FEATURES

|                                     |                                                                                                   |
|-------------------------------------|---------------------------------------------------------------------------------------------------|
| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor         |
| Metering Accuracy                   | ISO/IEC 62053-21 1%                                                                               |
| Metering per Input Line             | Yes                                                                                               |
| Metering per Branch Circuit Breaker | Yes                                                                                               |
| Metering per Output Receptacle      | No                                                                                                |
| Remote Outlet Switching             | No                                                                                                |
| Environmental Sensor Ready          | Yes                                                                                               |
| Replaceable Controller              | No                                                                                                |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure           |
| Networking                          | (10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)                                       |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC               |
| Cascading                           | Yes, Max 8 PDUs can be daisy chained using USB connection                                         |
| Onboard Display                     | 3-digit LED user-selectable display : Voltage, current, or active power (per line or per breaker) |
| Embedded Processor                  | ARM9 400MHZ (Atmel SAM9G20), 16MB NOR Flash, 64MB SDRAM                                           |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### INPUT

|                       |                                |
|-----------------------|--------------------------------|
| Input Plug            | NEMA L6-30P (2P3W)             |
| Cord Length           | 3 meters (9.84 feet) standard  |
| Cord Entry            | Rear feed                      |
| Cable Type            | IP44("splashproof")            |
| Number of Power Cords | 1                              |
| Maximum Input Current | 30A                            |
| Nominal Input Voltage | 208V                           |
| Rated Input Voltage   | 200 - 240V                     |
| Input Frequency       | 50/60Hz                        |
| Power Capacity        | 4.8kVA at 200V, 5.8kVA at 240V |

### OUTPUT

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Nominal Output Voltage           | 208V                                        |
| Rated Output Voltage             | 200 - 240V                                  |
| Receptacles (Output Connections) | (16) IEC320 C13, 12A<br>(4) IEC320 C19, 16A |
| Securelock Support               | Yes                                         |
| Cord Retention                   | No                                          |
| Overload Protection              | (2) LEGBX66-20                              |

### PHYSICAL

|                             |                                                 |
|-----------------------------|-------------------------------------------------|
| Color                       | Black powder coat (custom colors available)     |
| Unit Dimensions (WxDxH)     | 17.3" x 5.2" x 3.5" ; 440mm x 133mm x 88mm      |
| Unit Weight                 | 4.6 kg                                          |
| Shipping Weight             | 7.3 kg                                          |
| Shipping Dimensions (WxDxH) | 21.81" x 18.43" x 7.09" ; 554mm x 468mm x 180mm |
| Mounting                    | RACK-KIT-PX-1K 2U                               |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### ENVIRONMENTAL

|                             |           |
|-----------------------------|-----------|
| Operating Temperature       | 60°C      |
| Operating Relative Humidity | 85%       |
| Operating Elevation         | 0-10000ft |

### CONFORMANCE

|                      |                                                                              |
|----------------------|------------------------------------------------------------------------------|
| Regulatory Approvals | UL Listed, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant |
| Warranty             | Standard 2 years manufacturer warranty                                       |


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### CONTROL PANEL

Dimension: 72.85mm x 82mm




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### ELECTRICAL (ONE LINE) DIAGRAM




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### MECHANICAL DIAGRAM




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-1464R

rev20180620

### TRIP CURVE



This file generated on: Wed, June 20, 2018 - 05:33:21