

Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

LINE DRAWING



FEATURES

Energy Metering	Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor
Metering Accuracy	ISO/IEC 62053-21 1%
Metering per Input Line	Yes
Metering per Branch Circuit Breaker	Yes
Metering per Output Receptacle	Yes
Remote Outlet Switching	Yes
Environmental Sensor Ready	Yes
Replaceable Controller	No
Compatible Sensors	Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure
Networking	(10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)
Remote Management	HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC
Cascading	Yes, Max 8 PDUs can be daisy chained using USB connection
Onboard Display	3-digit LED user-selectable display : Voltage, current, or active power (per line, per breaker or per receptacle / outlet); Auto-flip orientation
Embedded Processor	ARM9 400MHZ (Atmel SAM9G20), 16MB NOR Flash, 64MB SDRAM

Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

INPUT

Input Plug	NEMA L6-30P (2P3W)
Cord Length	4 meters (13.12 feet)
Cord Entry	Bottom-front feed
Cable Type	IP44("splashproof")
Number of Power Cords	2
Maximum Input Current	30A
Nominal Input Voltage	208V
Rated Input Voltage	200 - 220V
Input Frequency	50/60Hz
Power Capacity	9.6kVA at 200V, 10.6kVA at 220V

OUTPUT

Nominal Output Voltage	208V
Rated Output Voltage	200 - 220V
Receptacles (Output Connections)	(28) IEC320 C13, 12A (4) IEC320 C19, 16A
Securelock Support	Yes
Cord Retention	Yes
Overload Protection	(4) [Moeller] FAZ-C20/2-NA

PHYSICAL

Color	Black powder coat (custom colors available)
Unit Dimensions (WxDxH)	3.5" x 2.8" x 36.5" ; 89mm x 71mm x 927mm
Unit Weight	8.3 kg
Shipping Weight	10 kg
Shipping Dimensions (WxDxH)	10.83" x 6.18" x 49.21" ; 275mm x 157mm x 1250mm
Mounting	Tool-less button mount

Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

ENVIRONMENTAL

Operating Temperature	60°C
Operating Relative Humidity	85%
Operating Elevation	0-10000ft

CONFORMANCE

Regulatory Approvals	UL Listed, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant
Warranty	Standard 2 years manufacturer warranty


Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

CONTROL PANEL

Dimension: 102.9mm x 79.6mm




Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

ELECTRICAL (ONE LINE) DIAGRAM




Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5

rev20170831

MECHANICAL DIAGRAM



Technical Specifications / Engineering Submittals

Raritan Model Number: PX2-5383X2-A4C5


rev20170831

TRIP CURVE

Miniature circuit-breakers

FAZ...


Tripping characteristic at 30 °C:
B, C, D to IEC/EN 60898



Miniature circuit-breakers

AZ...


Tripping characteristic at 30 °C:
C, D according to IEC/EN 60898



Combined RCD/MCB devices

PKNM-...

Tripping characteristic at 30 °C:
B, C according to IEC/EN 61009



Miniature circuit-breakers
Residual-current circuit-breakers