



- NOTES:
1. ALL DIMENSIONS ARE MILLIMETERS[INCHES].
 2. It can be installed lacing bar.



| | | |
|-----------|-----------|---------------|
| DRAWN : | Tom Hsueh | Aug. 27. 2014 |
| ENGINEER: | Tom Hsueh | Aug. 27. 2014 |
| APPROVED: | Tom Hsueh | Aug. 27. 2014 |



DO NOT SCALE DRAWING
SHEET 1 OF 1
 THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, INC. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, INC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

TITLE:
 iPDU Zero U,
 Three Phase, 48A/208V-240V
 Plug Type: IEC60309 60A 3P
 Outlet Type: (48)IEC320 C13

| | |
|------------------------|-----------|
| DWG NO. | REV. |
| MPX2-5765V-P1V2 | 0A |