


rev20250625

32A, 7.4kVA

### **LINE DRAWING**



#### **FEATURES**

Energy Metering	Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor	
Metering Accuracy	ISO/IEC 62053-21 1% (see page 3 for details)	
Metering per Input Line	Yes	
Metering per Branch Circuit Breaker	Yes	
Metering per Output Receptacle	Yes	
Remote Outlet Switching	No	
Environmental Sensor Ready	Yes	
Replaceable Controller	Yes	
Residual Current Monitoring	Yes, Type B (Single Channel detection of AC and DC leakage current (IEC62020 range: 15mA to 300mA) across all lines)	
Compatible Sensors	Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure	
Networking	Gigabit (10/100/1000 BaseT) Ethernet port; secondary, redundant (10/100/1000 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)	
Remote Management	HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP	
Cascading	Yes, Max 32 PDUs can be daisy chained using a USB connection and 32 PDUs using Ethernet connection	
Onboard Display	Color, matrix LCD display: Voltage, current, or active power (per line, per breaker, or per receptacle / outlet); Alarms; Configuration informati (name, ratings, IP / Networking information); Auto-flip orientation	
Embedded Processor	ARM Cortex A5 536MHZ (Atmel A5D35A), 16MB SPI Flash, 64MB DDR2 R	



rev20250625

### **INPUT**

Input Plug	IEC 60309 2P+E 6h 32A (2P3W), IP44	
Cord Length	3 meters (9.84 feet) standard	
Cord Entry	Bottom-bottom feed	
Cable Type	N-S LSOH 3G6.0	
Number of Power Cords	1	
Maximum Input Current	32A	
Nominal Input Voltage	230V	
Rated Input Voltage	200 - 240V	
Input Frequency	50/60Hz	
Power Capacity	6.4kVA at 200V, 7.7kVA at 240V	

### OUTPUT

Nominal Output Voltage	230V
Rated Output Voltage	200 - 240V
Receptacles (Output Connections)	(20) IEC320 C13, 10A (4) IEC320 C19, 16A
Securelock Support	Yes
Cord Retention	Yes
Overload Protection	(2) LEGBXA6-16, 5KAIC

### **PHYSICAL**

Color	Black powder coat (custom colors available)	
Unit Dimensions (WxDxH)	2.1" x 2.6" x 60.6" ; 52mm x 65mm x 1539mm	
Unit Weight	4.8 kg	
Shipping Weight	7.1 kg	
Shipping Dimensions (WxDxH)	9.06" x 4.65" x 71.61" ; 230mm x 118mm x 1819mm	
Mounting	G2-RACK-FOR-ZU	



rev20250625

### **ENVIRONMENTAL**

Operating Temperature	60°C
Operating Relative Humidity	85%
Operating Elevation	0-6000ft

### CONFORMANCE

Regulatory Approvals	CE, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant
Warranty	Standard 2 years manufacturer warranty


### **ACCURACY**

	Input Measurement	Output Measurement
LCD & GUI Current	±1% at 0.1 A resolution	±1% at 0.1 A resolution
Voltage	±1% at 0.1 V resolution	±1% at 0.1 V resolution
Active Power	±1% at 1 W resolution	±1% at 1 W resolution
Apparent Power	±1% at 1 VA resolution	±1% at 1 VA resolution
Power Factor	±1% at 0.1 resolution	±1% at 0.1 resolution
Active Energy	±1% at 0.1 kWh resolution	±1% at 0.1 kWh resolution
Branch Measurement		
Current	±1% at 0.1 A resolution	



rev20250625


### **CONTROL PANEL**





rev20250625

### **ELECTRICAL (ONE LINE) DIAGRAM**






### **Technical Specifications / Engineering Submittals**

Raritan Model Number: PX3-4493V-M11

rev20250625


#### **MECHANICAL DIAGRAM**





rev20250625


### Mounting Diagram (G2-RACK-FOR-ZU)





rev20250625

#### **TRIP CURVE**



This file generated on: Wed, June 25, 2025 - 03:12:35