



- NOTES:
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.
 2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.
 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS (INCHES).
 4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLLESS MOUNT FOR 3RD PARTY ENCLOSURE. BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.
 5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.
 6. KNOCKOUT SIZE (OPENING): 1.109" FOR $\phi 3/4"$ FLEXIBLE STEEL CONDUIT CABLE AND FITTING.
 7. DIMENSION TOLERANCE: LENGTH ± 0.3 MM, WIDTH ± 0.1 MM, DEPTH ± 0.5 MM.

<p>Raritan A brand of legrand</p>		PROJECTION THIRD ANGLE DO NOT SCALE DRAWING SHEET 1 OF 1	TITLE: iPDU Zero U Single Phase, 24A/200-240V Plug Type: 24A Terminal Outlet Type: Locking C13 (20), Locking C19 (4)	
			DWG NO.: MPX3-4497YV-E2 & MPX3-5497YV-E2 MODEL NO.: PX3-4497YV-E2 & PX3-5497YV-E2	
Drawing Maker: Eva_Lin Dec. 21, 2018 Design Engineer: Sam_L Dec. 21, 2018 Approver: Tom_H Dec. 21, 2018		THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.		REV. 2A