


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

### LINE DRAWING



### FEATURES

|                                     |   |
|-------------------------------------|---|
| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor   |
| Metering Accuracy                   | ISO/IEC 62053-21 1% (see page 3 for details)  |
| Metering per Input Line             | Yes   |
| Metering per Branch Circuit Breaker | No  |
| Metering per Output Receptacle      | Yes   |
| Remote Outlet Switching             | Yes   |
| Environmental Sensor Ready          | Yes   |
| Replaceable Controller              | No  |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure   |
| Networking                          | Gigabit (10/100/1000 BaseT) Ethernet port; secondary, redundant (10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)   |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP  |
| Cascading                           | Yes, Max 32 PDUs can be daisy chained using a USB connection and 32 PDUs using Ethernet connection  |
| Onboard Display                     | Color, matrix LCD display : Voltage, current, or active power (per line, or per receptacle /outlet); Alarms; Configuration information (name, ratings, IP / Networking information) |
| Embedded Processor                  | ARM Cortex A5 536MHZ (Atmel A5D35A), 16MB SPI Flash, 64MB DDR2 RAM  |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

### INPUT

|                       |                                |
|-----------------------|--------------------------------|
| Input Plug            | NEMA L5-20P (2P3W), IP44       |
| Cord Length           | 3 meters (9.84 feet) standard  |
| Cord Entry            | Rear feed                      |
| Cable Type            | VCT 3G3.5                      |
| Number of Power Cords | 1                              |
| Maximum Input Current | 20A                            |
| Nominal Input Voltage | 120V                           |
| Rated Input Voltage   | 100 - 120V                     |
| Input Frequency       | 50/60Hz                        |
| Power Capacity        | 1.6kVA at 100V, 1.9kVA at 120V |

### OUTPUT

|                                  |                      |
|----------------------------------|----------------------|
| Nominal Output Voltage           | 120V                 |
| Rated Output Voltage             | 100 - 120V           |
| Receptacles (Output Connections) | (20) NEMA 5-20R, 16A |
| Securelock Support               | No                   |
| Cord Retention                   | No                   |
| Overload Protection              | N/A                  |

### PHYSICAL

|                             |  |
|-----------------------------|--|
| Color                       | Black powder coat (custom colors available)      |
| Unit Dimensions (WxDxH)     | 17.3" x 11.5" x 3.5" ; 440mm x 293mm x 88mm      |
| Unit Weight                 | 5.1 kg   |
| Shipping Weight             | 9.3 kg   |
| Shipping Dimensions (WxDxH) | 22.05" x 21.73" x 11.18" ; 560mm x 552mm x 284mm |
| Mounting                    | RACK-KIT-PX-2U                                   |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

### ENVIRONMENTAL

|                             |          |
|-----------------------------|----------|
| Operating Temperature       | 60°C     |
| Operating Relative Humidity | 85%      |
| Operating Elevation         | 0-6000ft |

### CONFORMANCE

|                      |  |
|----------------------|--|
| Regulatory Approvals | UL Listed, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant |
| Warranty             | Standard 2 years manufacturer warranty                                       |

### ACCURACY


|                   | Input Measurement         | Output Measurement        |
|-------------------|---------------------------|---------------------------|
| LCD & GUI Current | ±1% at 0.1 A resolution   | ±1% at 0.1 A resolution   |
| Voltage           | ±1% at 0.1 V resolution   | ±1% at 0.1 V resolution   |
| Active Power      | ±1% at 1 W resolution     | ±1% at 1 W resolution     |
| Apparent Power    | ±1% at 1 VA resolution    | ±1% at 1 VA resolution    |
| Power Factor      | ±1% at 0.1 resolution     | ±1% at 0.1 resolution     |
| Active Energy     | ±1% at 0.1 kWh resolution | ±1% at 0.1 kWh resolution |

## Technical Specifications / Engineering Submittals


Raritan Model Number: PX3-5407R

rev20250625

### CONTROL PANEL



### CONTROL PANEL2




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

### ELECTRICAL (ONE LINE) DIAGRAM




# Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

## MECHANICAL DIAGRAM



## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5407R

rev20250625

### TRIP CURVE

This file generated on: Wed, June 25, 2025 - 03:29:44