



- NOTES:

 1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.

 2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.

 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLITERS [INCHES].

 4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLESS MOUNT FOR 3RD PARTY ENCLOSURE.

 BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.

 5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.

 6. LENGTH OF THE CORD IS 3000MM+/-70MM

 7. DIMENSION TOLERANCE: LENGTH +/-3MM, WIDTH +/-1MM, DEPTH +/-0.5MM

Drawing Maker:	EVA LIN	Aug. 22, 2016
Design Engineer:	Kenny_C	Aug. 22, 2016
Approver:	Tom_H	Aug. 22, 2016

(4)	$\overline{}$
W	V

PROJECTION THIRD ANGLE DO NOT SCALE DRAWING SHEET 1 OF 1

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, INC. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, INC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

TITLE:

iPDU Zero U Single Phase, 24A/200-240V Plug Type:NEMA L6-30P Outlet Type:(20)IEC320 C13

PX3-5460V & PX3-4460V

REV. 0B