


rev20250625

### **LINE DRAWING**



#### **FEATURES**

| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA),<br>Energy (kWh), Power Factor   |  |
|-------------------------------------|--|--|
| Metering Accuracy                   | ISO/IEC 62053-21 1% (see page 3 for details)   |  |
| Metering per Input Line             | Yes  |  |
| Metering per Branch Circuit Breaker | Yes  |  |
| Metering per Output Receptacle      | Yes  |  |
| Remote Outlet Switching             | Yes  |  |
| Environmental Sensor Ready          | Yes  |  |
| Replaceable Controller              | No   |  |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water<br>Leak, and Contact Closure   |  |
| Networking                          | Gigabit (10/100/1000 BaseT) Ethernet port; secondary, redundant (10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)  |  |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP   |  |
| Cascading                           | Yes, Max 32 PDUs can be daisy chained using a USB connection and 32 PDUs using Ethernet connection   |  |
| Onboard Display                     | Color, matrix LCD display: Voltage, current, or active power (per line, per breaker, or per receptacle / outlet); Alarms; Configuration information (name, ratings, IP / Networking information) |  |
| Embedded Processor                  | ARM Cortex A5 536MHZ (Atmel A5D35A), 16MB SPI Flash, 64MB DDR2   |  |
| ibedded Flocessol                   | ARM COITEX AS SSOMEZ (Attriet ASDSSA), TOMB SPI Flash, 04MB D  |  |



rev20250625

### **INPUT**

| Input Plug            | Cord (N/A)                     |
|-----------------------|--------------------------------|
| Cord Length           | 3 meters (9.84 feet) standard  |
| Cord Entry            | Rear feed                      |
| Cable Type            | N/A                            |
| Number of Power Cords | 1                              |
| Maximum Input Current | 32A                            |
| Nominal Input Voltage | 230V                           |
| Rated Input Voltage   | 200 - 240V                     |
| Input Frequency       | 50/60Hz                        |
| Power Capacity        | 6.4kVA at 200V, 7.7kVA at 240V |
|                       |                                |

### **OUTPUT**

| Nominal Output Voltage           | 230V  |
|----------------------------------|---|
| Rated Output Voltage             | 200 - 240V                                  |
| Receptacles (Output Connections) | (16) IEC320 C13, 10A<br>(4) IEC320 C19, 16A |
| Securelock Support               | Yes   |
| Cord Retention                   | No  |
| Overload Protection              | (2) LEGBX6-16, 5KAIC                        |

### **PHYSICAL**

| Color                       | Black powder coat (custom colors available)      |  |
|-----------------------------|--|--|
| Unit Dimensions (WxDxH)     | 17.3" x 11.5" x 3.5" ; 440mm x 293mm x 88mm      |  |
| Unit Weight                 | TBD  |  |
| Shipping Weight             | TBD  |  |
| Shipping Dimensions (WxDxH) | 21.81" x 17.87" x 10.39" ; 554mm x 454mm x 264mm |  |
| Mounting                    | RACK-KIT-PX-2U                                   |  |
|                             |  |  |



rev20250625

### **ENVIRONMENTAL**

| Operating Temperature       | 60°C     |
|-----------------------------|----------|
| Operating Relative Humidity | 85%      |
| Operating Elevation         | 0-6000ft |

### CONFORMANCE

| Regulatory Approvals | CE, Canada ICES-003, Part 15 Class A of the FCC rules,<br>RoHS compliant |  |
|----------------------|--|--|
| Warranty             | Standard 2 years manufacturer warranty                                   |  |


### **ACCURACY**

|                    | Input Measurement         | Output Measurement        |
|--------------------|---------------------------|---------------------------|
| LCD & GUI Current  | ±1% at 0.1 A resolution   | ±1% at 0.1 A resolution   |
| Voltage            | ±1% at 0.1 V resolution   | ±1% at 0.1 V resolution   |
| Active Power       | ±1% at 1 W resolution     | ±1% at 1 W resolution     |
| Apparent Power     | ±1% at 1 VA resolution    | ±1% at 1 VA resolution    |
| Power Factor       | ±1% at 0.1 resolution     | ±1% at 0.1 resolution     |
| Active Energy      | ±1% at 0.1 kWh resolution | ±1% at 0.1 kWh resolution |
| Branch Measurement |                           |                           |
| Current            | ±1% at 0.1 A resolution   |                           |
|                    |                           |                           |




rev20250625

### **CONTROL PANEL**



### **CONTROL PANEL2**






### **Technical Specifications / Engineering Submittals**

Raritan Model Number: PX3-5469NR

rev20250625


### **ELECTRICAL (ONE LINE) DIAGRAM**





rev20250625


#### **MECHANICAL DIAGRAM**





rev20250625

#### **TRIP CURVE**



This file generated on: Wed, June 25, 2025 - 03:31:05