

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### LINE DRAWING



### FEATURES

|                                     |                                                                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor                                                                                                                                |
| Metering Accuracy                   | ISO/IEC 62053-21 1%                                                                                                                                                                                                      |
| Metering per Input Line             | Yes                                                                                                                                                                                                                      |
| Metering per Branch Circuit Breaker | Yes                                                                                                                                                                                                                      |
| Metering per Output Receptacle      | Yes                                                                                                                                                                                                                      |
| Remote Outlet Switching             | Yes                                                                                                                                                                                                                      |
| Environmental Sensor Ready          | Yes                                                                                                                                                                                                                      |
| Replaceable Controller              | Yes                                                                                                                                                                                                                      |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure                                                                                                                                  |
| Networking                          | Gigabit (10/100/1000 BaseT) Ethernet port                                                                                                                                                                                |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC                                                                                                                                      |
| Cascading                           | Yes, Max 16 PDUs can be daisy chained using USB connection                                                                                                                                                               |
| Onboard Display                     | Color, matrix LCD display : Voltage, current, or active power (per line, per breaker, or per receptacle / outlet); Alarms; Configuration information (name, ratings, IP / Networking information); Auto-flip orientation |
| Embedded Processor                  | ARM9 400MHZ (Atmel SAM9G20), 16MB NOR Flash, 64MB SDRAM                                                                                                                                                                  |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### INPUT

|                       |                                |
|-----------------------|--------------------------------|
| Input Plug            | Clipsal 56P332 (2P3W)          |
| Cord Length           | 3 meters (9.84 feet) standard  |
| Cord Entry            | Bottom-front feed              |
| Cable Type            | IP66                           |
| Number of Power Cords | 1                              |
| Maximum Input Current | 32A                            |
| Nominal Input Voltage | 240V                           |
| Rated Input Voltage   | 240 - 240V                     |
| Input Frequency       | 50/60Hz                        |
| Power Capacity        | 7.7kVA at 240V, 7.7kVA at 240V |

### OUTPUT

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Nominal Output Voltage           | 240V                                        |
| Rated Output Voltage             | 240 - 240V                                  |
| Receptacles (Output Connections) | (18) IEC320 C13, 10A<br>(6) IEC320 C19, 16A |
| Securelock Support               | Yes                                         |
| Cord Retention                   | Yes                                         |
| Overload Protection              | (2) LEGBXA6-16                              |

### PHYSICAL

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| Color                       | Black powder coat (custom colors available)      |
| Unit Dimensions (WxDxH)     | 2.1" x 2.6" x 60.6" ; 52mm x 65mm x 1539mm       |
| Unit Weight                 | 6 kg                                             |
| Shipping Weight             | 8 kg                                             |
| Shipping Dimensions (WxDxH) | 11.02" x 4.53" x 65.16" ; 280mm x 115mm x 1655mm |
| Mounting                    | G2-RACK-FOR-ZU                                   |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### ENVIRONMENTAL

|                             |           |
|-----------------------------|-----------|
| Operating Temperature       | 60°C      |
| Operating Relative Humidity | 85%       |
| Operating Elevation         | 0-10000ft |

### CONFORMANCE

|                      |                                                                       |
|----------------------|-----------------------------------------------------------------------|
| Regulatory Approvals | CE, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant |
| Warranty             | Standard 2 years manufacturer warranty                                |


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### CONTROL PANEL

Dimension: 212mm x 43.5mm




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### ELECTRICAL (ONE LINE) DIAGRAM




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### MECHANICAL DIAGRAM





## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1


rev20170831

### Mounting Diagram (G2-RACK-FOR-ZU)



250-70-0104-00






250-80-0011-00



**250-70-0007-00**



**250-70-0093-00**




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5498A3-G1

rev20170831

### TRIP CURVE



This file generated on: Thu, August 31, 2017 - 21:41:02