


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### LINE DRAWING



### FEATURES

|                                     |                                                                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor                                                                                                                                |
| Metering Accuracy                   | ISO/IEC 62053-21 1%                                                                                                                                                                                                      |
| Metering per Input Line             | Yes                                                                                                                                                                                                                      |
| Metering per Branch Circuit Breaker | Yes                                                                                                                                                                                                                      |
| Metering per Output Receptacle      | Yes                                                                                                                                                                                                                      |
| Remote Outlet Switching             | Yes                                                                                                                                                                                                                      |
| Environmental Sensor Ready          | Yes                                                                                                                                                                                                                      |
| Replaceable Controller              | Yes                                                                                                                                                                                                                      |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure                                                                                                                                  |
| Networking                          | (10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)                                                                                                                                                              |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP                                                                                                                     |
| Cascading                           | Yes, Max 16 PDUs can be daisy chained using USB connection                                                                                                                                                               |
| Onboard Display                     | Color, matrix LCD display : Voltage, current, or active power (per line, per breaker, or per receptacle / outlet); Alarms; Configuration information (name, ratings, IP / Networking information); Auto-flip orientation |
| Embedded Processor                  | ARM9 400MHZ (Atmel SAM9G20), 16MB NOR Flash, 64MB SDRAM                                                                                                                                                                  |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### INPUT

|                       |                                  |
|-----------------------|----------------------------------|
| Input Plug            | CS8365C (3P4W)                   |
| Cord Length           | 3 meters (9.84 feet) standard    |
| Cord Entry            | Bottom-front feed                |
| Cable Type            | IP20                             |
| Number of Power Cords | 1                                |
| Maximum Input Current | 50A                              |
| Nominal Input Voltage | 208V 3 phase                     |
| Rated Input Voltage   | 208 - 240V 3 phase               |
| Input Frequency       | 50/60Hz                          |
| Power Capacity        | 14.4kVA at 208V, 16.6kVA at 240V |

### OUTPUT

|                                  |                      |
|----------------------------------|----------------------|
| Nominal Output Voltage           | 208V                 |
| Rated Output Voltage             | 208 - 240V           |
| Receptacles (Output Connections) | (24) IEC320 C13, 12A |
| Securelock Support               | Yes                  |
| Cord Retention                   | Yes                  |
| Overload Protection              | (6) LEGBX66-20       |

### PHYSICAL

|                             |                                             |
|-----------------------------|---------------------------------------------|
| Color                       | Black powder coat (custom colors available) |
| Unit Dimensions (WxDxH)     | 2.3" x 2.8" x 70.1" ; 59mm x 71mm x 1780mm  |
| Unit Weight                 | 9.8 kg                                      |
| Shipping Weight             | 12.6 kg                                     |
| Shipping Dimensions (WxDxH) | TBD                                         |
| Mounting                    | Tool-less button mount                      |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### ENVIRONMENTAL

|                             |           |
|-----------------------------|-----------|
| Operating Temperature       | 60°C      |
| Operating Relative Humidity | 85%       |
| Operating Elevation         | 0-10000ft |

### CONFORMANCE

|                      |                                                                              |
|----------------------|------------------------------------------------------------------------------|
| Regulatory Approvals | UL Listed, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant |
| Warranty             | Standard 2 years manufacturer warranty                                       |


## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### CONTROL PANEL

Dimension: 212mm x 43.5mm




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### ELECTRICAL (ONE LINE) DIAGRAM




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### MECHANICAL DIAGRAM




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5540-M10N5

rev20180620

### TRIP CURVE



This file generated on: Wed, June 20, 2018 - 05:43:29