



- NOTES:
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.
  2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.
  3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
  4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLLESS MOUNT FOR 3RD PARTY ENCLOSURE. BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.
  5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.
  6. RARITAN STANDARD LENGTH OF THE CORD IS 3000MM +/-70MM
  7. DIMENSION TOLERANCE: LENGTH +/-3MM, WIDTH +/-1MM, DEPTH +/-0.5MM

 A brand of 		PROJECTION THIRD ANGLE	DO NOT SCALE DRAWING	SPECIFICATION <b>iPDU Zero U</b> 380-415V 3Φ-Y, 24A Plug Type: IEC60309 32A 3PY (UL) Outlet Type: C13 (48), C19 (6)
			SHEET 1 OF 1	
Drawing Maker: Eva Lin Design Engineer: Eva Lin Approver: Tom_H	JUN. 16, 2021 JUN. 16, 2021 JUN. 16, 2021	THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.		DWG NO. MPX3-596112U-V2 & MPX3-496112U-V2  MODEL NO. <b>PX3-596112U-V2 &amp; PX3-496112U-V2</b> PX3-596112U-01V2 & PX3-496112U-01V2
			REV.	<b>2C</b>